



# 2PART PCM-17

## Polymer Cementitious Membrane

The information contained within this MSDS details health and safety hazard information of the product and how to safely handle and use the product in the workplace. Each user of this product should read this MSDS and consider the information in the context of how the product will be handled and used in the workplace including in conjunction with other products. If clarification or further information is needed to ensure that an appropriate risk assessment can be made, the user should contact Demtech Australia Pty Ltd. Demtech Australia Pty Ltd makes no representation as to the completeness and accuracy of the data contained in this data sheet. It is the user's obligation to evaluate and use this product safely, and to comply with all relevant Federal, State and Local Government laws and regulations. Demtech Australia Pty Ltd shall not be responsible for loss, damage or injury resulting from reliance upon or failure to adhere to any recommendation or information contained herein, from abnormal use of the material, or any hazard inherent in the nature of the material.

### STATEMENT OF HAZARDOUS NATURE

Not classified as hazardous according to criteria of Worksafe Australia.

### IDENTIFICATION

Product Name	2 Part PCM-17 Polymer Cementitious Membrane
Other Names	None
UN Number	None
Dangerous Goods Class	None assigned
Subsidiary Risk	None assigned
Shipping Name	None assigned
Hazchem Code	None assigned
Poisons Schedule Number	None assigned

### DESCRIPTION

Cureflex - 2PART PCM-17 is a fast drying "2PART" waterproof membrane that is suitable for a wide range of waterproofing applications. It consists of Part A (liquid) and Part B (dry powder). Cureflex - 2PART PCM-17 uses a new technique in "Cross-Collateralisation" in (PPT) Powdered Polymer Technology, provides outstanding adhesion properties over a variety of building substrates such as; concrete, masonry, Hebel panels, renders, compressed sheeting, cement sheet underlays, villa board, cement based compounds and all grade plaster board. Cureflex - 2PART PCM-17 also offers excellent surface adhesion properties for typical overlaid finishes such as screeds, renders and tile adhesives.





# 2PART PCM-17

## Polymer Cementitious Membrane

### PHYSICAL DESCRIPTION / PROPERTIES

Appearance	Light grey
Compressive Strength	-
Flexural Strength	-
Bond Strength	1.7MPa (to concrete)
Setting Time	5-7 hours (dry film)
Working Time	60 minutes
Application Temperatures	Above 5 deg C and below 30 deg C (surface temp)
Coverage	1.5litres per m2 for general areas. 2litres per m2 for immersed areas
Classification	Class 11

### PREPARATION / APPLICATION

Surface Preparation	Clean Substrates. Surfaces must free of contaminants or foreign material. Ensure substrate is sound and free of any loose or unsecured areas prior to application
Priming	Surfaces to be primed using Demtech proprietary primers. For porous surfaces use Cureflex PG57 primer. For non porous surfaces use Cureflex.
Mixing	Cureflex PCM-17 is formed by mixing 1kg of Part A liquid to 1.5kg of Part B dry. Use an electric stirrer with paddle and mix until a smooth, lump free consistency is formed.
Curing	Recoat: 1-3 hours Dry film: 5-7 hours Tile/toppings over: 24 hours Immersion: 21 days
Application	<p>Cureflex PCM-17 requires a suitable bondbreaker at substrate junctions. Flexiban Joint Bandage or RF webbing tape is recommended. Apply with brush, roller or sprayer.</p> <p>Recommended coverage will differ based on application use:            General waterproofing - minimum 1.5mm dried film thickness is required - 1litre/1.25kg/m2 per mm layer thickness.            Immersed applications a thickness of 2mm is required - 1litre/1.25kg/m2 per mm layer thickness</p>
Precautions	<p>Not to be used as an exposed membrane coating in areas subject to UV. Not designed as a trafficable membrane coating. Not to be used in areas subject to negative hydrostatic conditions. Do not apply when rain is imminent.</p> <p>Do not apply when surface temperatures are below 5 deg C or above 30 deg C All finished coatings over this membrane are to be water based and solvent free. Polymer modified cement based adhesives and enhanced toppings to be used directly over.</p>

# 2PART PCM-17

## Polymer Cementitious Membrane

### PHYSICAL DESCRIPTION / PROPERTIES

Substrates	Substrate Surfaces must be clean, free of gypsum and foreign matter including oil and wax residues. Surfaces must be in a sound and stable state prior to commencing the application.
Clean Up	Clean up with water while wet. Once dried product will need to be mechanically removed.

### HEALTH HAZARD INFORMATION

Health Effects <i>Chronic:</i>	Due to cement content, long term exposure to high dust concentrations may cause irritation to lungs and result in breathing disorders, as cement and silica is now classified as carcinogenic. Contact with skin, inhalation of dust, vapour ingestion in any form should be avoided. Sensitisation may result in allergic dermatitis responses including rash, itching, swelling of extremities, redness & irritation. Principal routes of exposure are by accidental skin and eye contact and by inhalation of dusts. As with any powdered chemical product, contact with unprotected bare skin; inhalation of dusts in work place atmosphere; or ingestion in any form, should be avoided by observing good occupational work practice.
Swallowed	Material is irritating and mildly corrosive if swallowed. Ingestion may result in nausea, abdominal irritation, pain and vomiting.
Eye	Prolonged exposure may cause eye irritation or burning and may cause conjunctivitis.
Skin	Prolonged exposure may result in slight skin irritation and or drying and may lead to dermatitis or may cause sensitisation.
Inhaled	Excessive exposure to dusts can cause damage to health and lungs slight irritation to eyes, nose and throat. Dust is irritating to upper respiratory tract and lungs. Over exposure to irrespirable dust may cause coughing, wheezing and irritation to the nasal passages.

### FIRST AID

Swallowed	Rinse mouth then provide water slowly. If poisoning occurs, seek medical assistance immediately, contact doctor or poisons information centre. Do not induce vomiting. Material highly irritating and mildly corrosive if swallowed.
Eye	Immediately flush with large amounts of water for at 5-10 minutes; lifting upper and lower lids. Seek medical attention if irritation persists.
Skin	Wash with water and soap. Seek medical attention if irritation persists.
Inhaled	If affected, move subject to fresh air. Seek medical assistance if symptoms persist.
First Aid Facilities	Ensure availability of eye wash fountains and/or water access.
Advice to Doctor	Treat symptomatically.

# 2PART PCM-17

## Polymer Cementitious Membrane

### PRECAUTIONS FOR USE

#### Personal Protection

Respirator Type (AS/NZS 1716)	Where concentrations in air may exceed the recommended exposure limits, or work practice or other means of exposure reduction are not adequate, approved respirator may be necessary to prevent overexposure by inhalation.
Eye Protection	Safety glasses
Clothing	Protective clothing to cover body parts, e.g. long sleeved overalls or similar; and boots.
Other	Wash hands before smoking, eating, drinking or using the toilet and after finishing work. Observe the usual precautions when handling chemicals.
Flammability Fire Hazards	Product is non flammable according to the Australian Code for the Transport of Dangerous Goods.

### SAFE HANDLING INFORMATION

#### Storage & Transport

Location	Store in a dry cool area to prolong storage life.
Temperature Conditions	Best stored at room temperature; Prevent from freezing.
Protection from Weather	Store undercover and away from heat sources, water and electric plant.
Storage Incompatibilities	Store undercover and away from heat sources, water and electric plant.

#### Spills & Disposal

Clean Up Spills	Clean up with water. Use solvent cleaners if product has dried. Do not contaminate streams, rivers, or water courses. Do not flush down drains and sewers. Inform local authority if product enters drains, sewers, streams, etc. Sweep and wipe all trace elements.
Disposal	Dispose of in accordance with Local, State and Federal regulations.
Precautions for Clean Up Crew	Nitrile rubber or PVC gloves, safety glasses and respirator.

#### Fire / Explosion Hazard

Hazard of Use / Storage	Non Combustible. Not considered a fire risk.
List of Dangerous Decomposition or Combustion Products	None
Types of Extinguisher	No Restriction Listed - Water, Foam, CO2 and Dry Chemical
Precautions	Fire fighters should wear self-contained breathing apparatus.
Protective Clothing	None
Reactivity	None

Demtech Australia Pty Ltd  
P.O. Box 4535 Knox City  
Centre VIC 3152



# 2PART PCM-17

## Polymer Cementitious Membrane

### OTHER INFORMATION

Ecology	Avoid contaminating waterways and sewers.
Packaging & Labelling	Dry powder 15kg Poly lined Valve Bag stored in empty mixing bucket. Liquid additive 10kg Pail.
Precautions for Use	No special precautions
Reactivity Data	None
Toxicity Data	None

### CONTACT POINT

Technical Department  
Demtech Australia Pty Ltd (ABN : 91 131 136 706)  
16 Logis Blvd, Dandenong South 3175  
P: 1300 300 090  
Email: info@demtech.com.au

Australia Poisons Information Centre	13 11 26
Police & Fire Brigade	000

General	The information contained herein is based on present state of our knowledge and does not guarantee certain properties. Recipients of our products must take responsibility for observing laws and regulations. The information contained within is published free of charge in good faith and is based on technical data that Demtech Australia Pty Ltd considers to be reliable.
---------	---

**Disclaimer**  
The information within is intended for use by skilled and/or persons with technical knowledge. They required to make their own assessment and use product at their own risk and discretion. Information contained in this product sheet conforms to the standard detail recommendations and specification for the use of Demtech Australia products as of the date of this document. Demtech Australia Pty Ltd make no other warranties and assumes no liability, expressed or implied.

To ensure that you are using the most complete and up to date information, contact Demtech Australia Pty Ltd.

Demtech Australia Pty Ltd  
P.O. Box 4535 Knox City  
Centre VIC 3152

www.demtech.com.au  
info@demtech.com.au  
Technical Support: 1300 300 090