

LS151 Primer Resurfacing Primer

The information contained within this Technical Data, details product description, health and safety hazard information of the product and how to safely handle and use the product in the workplace. Also refer to MSDS for more information. Each user of this product should read the MSDS and consider the information in the context of how the product will be handled and used in the workplace including in conjunction with other products. If clarification or further information is needed to ensure that an appropriate risk assessment can be made, the user should contact Demtech Australia Pty Ltd. Demtech Australia Pty Ltd makes no representation as to the completeness and accuracy of the data contained in this data sheet. It is the user's obligation to evaluate and use this product safely, and to comply with all relevant Federal, State and Local Government laws and regulations. Demtech Australia Pty Ltd shall not be responsible for loss, damage or injury resulting from reliance upon or failure to adhere to any recommendation or information contained herein, from abnormal use of the material, or any hazard inherent in the nature of the material.

STATEMENT OF HAZARDOUS NATURE

Not classified as hazardous according to criteria of Worksafe Australia.

IDENTIFICATION

Product Name	CUREFLEX - LS151 Resurfacing Primer
Other Names	None
Manufacturer's Product Code	LS151
UN Number	None assigned
Dangerous Goods Class	None assigned
Subsidiary Risk	None assigned
Shipping Name	None assigned
Hazchem Code	None assigned
Poisons Schedule Number	None assigned
Major recommended uses	Primer Coat



LS151 Primer Resurfacing Primer

IDENTIFICATION Cont.

Physical Description / Properties

Appearance	Wet – blue gritty paste; Dry – light blue film coating
Boiling Point (°C)	100°C approx. (water)
Vapour Pressure	23 hPa @ 20°C
Volatile Component	Not Determined
Specific Gravity	1.3
Flashpoint (°C)	N/A
Viscosity	2000 mPa.s
Solubility in Water	Completely Miscible

Other Properties

Evaporation Rate	Slower than butyl acetate
Vapour Density	Heavier than air
Form	Liquid
Stability	Stable
Hazardous Polymerisation	Will not occur
Materials to avoid	Strong acids & oxidizing agents

INGREDIENTS

Chemical Name:	CAS Number:	Proportion:
Alkyl acrylate--styrene copolymer	-	50.00 - 60.00%
Sodium hydroxide	1310 -73-2	0 - 0.20%
Styrene	100-42-5	0 - 0.10%

Contents: High >60% - Medium 10 – 60% - Low 1 – 10% - Very Low <1%

* Other ingredients determined not to be hazardous, including water, to 100%.

LS151 Primer Resurfacing Primer

HEALTH HAZARD INFORMATION

Health Effects

Acute:	
Swallowed	No data supplied; but polymer is not expected to be harmful.
Eye	May be an eye irritant
Skin	Prolonged or repeated contact with skin may result in slight skin irritation.
Inhaled	Excessive exposure to vapours or spray mist may cause slight irritation to eyes, nose and throat.
Chronic:	Principal routes of exposure are by accidental skin and eye contact and by inhalation of vapours especially at higher temperatures. As with any chemical product, contact with unprotected bare skin; inhalation of vapour, mist or dust in work place atmosphere; or ingestion in any form, should be avoided by observing good occupational work practice.

First Aid

Swallowed	Give plenty of water. Seek medical assistance. Decision on induction of vomiting to be made by qualified person.
Eye	Immediately flush with large amounts of water for at 5-10 minutes; lifting upper and lower lids. Seek medical attention if irritation persists.
Skin	Wash with water and soap. Seek medical attention if irritation persists.
Inhaled	If affected, move subject to fresh air. Seek medical assistance if symptoms persist.
First Aid Facilities	Ensure availability of eye wash fountains and/or water access.
Advice to Doctor	Treat symptomatically.

LS151 Primer Resurfacing Primer

PRECAUTIONS FOR USE

Exposure Standards - As established by the NOHSC

Chemical Name:	STL:		TWA:	
	mg/m ³	ppm	mg/m ³	ppm
Sodium Hydroxide	-	-	2	-
Styrene	140	30	75	10

* **Other Exposure information:** Exposure standards not established for product, or other ingredients.

Engineering Controls	General ventilation is recommended during normal use. Local ventilation may be required during certain operations to prevent inhalation of vapours.
-----------------------------	---

Personal Protection

Respirator Type (AS/NZS 1716)	Where concentrations in air may exceed the recommended exposure limits, or work practice or other means of exposure reduction are not adequate, approved respirator may be necessary to prevent overexposure by inhalation.
Glove Type	Neoprene/rubber gloves.
Eye Protection	Safety Glasses As Appropriate
Clothing	Protective clothing to cover body parts, e.g. long sleeved overalls or similar; and boots.
Other	Wash hands before smoking, eating, drinking or using the toilet and after finishing work. Observe the usual precautions when handling chemicals.
Flammability Fire Hazards	Product is non flammable according to the Australian Code for the Transport of Dangerous Goods.

SAFE HANDLING INFORMATION

Storage & Transport

Location	Store in a dry cool area to prolong storage life.
Temperature Conditions	Best stored at room temperature; Prevent from freezing.
Protection from Weather	Store undercover and away from heat sources, water and electric plant.
Storage Incompatibilities	N/A

Demtech Australia Pty Ltd
P.O. Box 4535 Knox City
Centre VIC 3152

LS151 Primer Resurfacing Primer

SPILLS AND DISPOSAL

Clean Up Spills / Leaks While product remains wet, floors will be slippery. Caution must be taken.
Small spills: Wipe up and wash area with water.
Large spills: Dike and contain spill with sand or earth.
 Do not contaminate streams, rivers, or water courses. Do not flush down drains and sewers. Inform local authority if liquid enters drains, sewers, streams, etc. Clean up before the material dries. Absorb the liquid with sand, earth or other absorbent. Place used absorbent in suitable, sealable labelled containers.

Disposal	Dispose of in accordance with Local, State and Federal regulations.
----------	---

Precautions for Clean Up Crew	Nitrile rubber or PVC gloves.
-------------------------------	-------------------------------

FIRE / EXPLOSION HAZARDS

Hazard of Use / Storage	Product will not support combustion. Polymer will burn in a general fire, once all the water has been driven off.
-------------------------	---

List of Dangerous Decomposition or Combustion Products	Carbon monoxide, carbon dioxide, oxides of nitrogen, fumes and smoke.
--	---

Types of Extinguisher	Water, Foam, CO2 and Dry Chemical.
-----------------------	------------------------------------

Precautions	Fire fighters should wear self-contained breathing apparatus.
-------------	---

Protective Clothing	None
---------------------	------

Reactivity	None
------------	------

OTHER INFORMATION

Ecology	Avoid contaminating waterways and sewers.
---------	---

Packaging & Labelling	1.2, 5 & 15 litre pails
-----------------------	-------------------------



LS151 Primer Resurfacing Primer

CONTACT POINT

Technical Department

Demtech Australia Pty Ltd (ABN : 91 131 136 706)
16 Logis Blvd, Dandenong South 3175
P: 1300 300 090
Email: info@demtech.com.au

Australia Poisons Information Centre

13 11 26

Police & Fire Brigade

000

General

The information contained herein is based on present state of our knowledge and does not guarantee certain properties. Recipients of our products must take responsibility for observing laws and regulations. The information contained within is published free of charge in good faith and is based on technical data that Demtech Australia Pty Ltd considers to be reliable.

Disclaimer

The information within is intended for use by skilled and/or persons with technical knowledge. They required to make their own assessment and use product at their own risk and discretion. Information contained in this product sheet conforms to the standard detail recommendations and specification for the use of Demtech Australia products as of the date of this document. Demtech Australia Pty Ltd make no other warranties and assumes no liability, expressed or implied.

To ensure that you are using the most complete and up to date information, contact Demtech Australia Pty Ltd.

Demtech Australia Pty Ltd
P.O. Box 4535 Knox City
Centre VIC 3152